



PRODOTTO	FINITURA	PESO (g/m²)	H. CM.	MT.	DATI TECNICI	RESISTENZA (N/5 cm)	CODICE	STAMPA	1 rotolo da 50 €/mq	da 49 a 11 mt €/mq	da 10 a 1 mt €/mq
INTERCast FRONTLIT	opaco	450	1,60	50	18*13 1000*1000 D	2200/1900	CT-FL450-32L5	E L U	2,48	3,57	3,71
	opaco	450	3,20	50	18*13 1000*1000 D	2200/1900	CT-FL450-16L5	E L U	2,48	3,57	3,71
									1 rotolo da 30 €/mq	da 29 a 15 mt €/mq	da 14 a 1 mt €/mq
	opaco	510	1,12	30	20*20 1000*1000 D	2200/1900	CT-FL510-11L3	E L U	3,29	4,73	4,92
	opaco	510	1,37	30	20*20 1000*1000 D	2200/1900	CT-FL510-13L3	E L U	3,29	4,73	4,91
	opaco	510	1,60	30	20*20 1000*1000 D	2200/1900	CT-FL510-16L3	E L U	3,29	4,72	4,91
									1 rotolo da 50 €/mq	da 49 a 11 mt €/mq	da 10 a 1 mt €/mq
	opaco	510	3,20	50	20*20 1000*1000 D	2200/1900	CT-FL510-32L5	E L U	3,29	-----	-----
									1 rotolo da 30 €/mq	da 29 a 15 mt €/mq	da 14 a 1 mt €/mq
	opaco 	510	1,12	30	20*20 1000*1000 D	2200/1900	CT-FL510-11L3-B1	E L U	3,93	5,65	5,87
	opaco 	510	1,37	30	20*20 1000*1000 D	2200/1900	CT-FL510-13L3-B1	E L U	3,93	5,65	5,88
	opaco 	510	1,60	30	20*20 1000*1000 D	2200/1900	CT-FL510-16L3-B1	E L U	3,93	5,65	5,88
									1 rotolo da 50 €/mq	da 49 a 11 mt €/mq	da 10 a 1 mt €/mq
	opaco 	510	3,20	50	20*20 1000*1000 D	2200/1900	CT-FL510-32L5-B1	E L U	3,93	-----	-----
									1 rotolo da 30 €/mq	da 29 a 15 mt €/mq	da 14 a 1 mt €/mq
	opaco	560	1,12	30	28*28 500*500 D	2200/1900	CT-FL560-11L3	E L U	3,70	5,31	5,52
	opaco	560	1,37	30	28*28 500*500 D	2200/1900	CT-FL560-13L3	E L U	3,70	5,31	5,53
	opaco	560	1,60	30	28*28 500*500 D	2200/1900	CT-FL560-16L3	E L U	3,70	-----	-----

PRODOTTO	FINITURA	PESO (g/m²)	H. CM.	MT.	DATI TECNICI	RESISTENZA (N/5 cm)	CODICE	STAMPA	1 rotolo da 30 €/mq	da 29 a 15 mt €/mq	da 14 a 1 mt €/mq
BLACKBACK 	opaco retro nero	510	1,12	30	20*20 1000*1000 D	2200/1900	CT-FLBB510-11L3 ESAURIMENTO	E L U	4,11	5,91	6,15
	opaco retro nero	510	1,37	30	20*20 1000*1000 D	2200/1900	CT-FLBB510-13L3 ESAURIMENTO	E L U	4,12	5,92	6,15
	opaco retro nero	510	1,60	30	20*20 1000*1000 D	2200/1901	CT-FLBB510-16L3 ESAURIMENTO	E L U	4,11	5,91	6,15

PRODOTTO	FINITURA	PESO (g/m²)	H. CM.	MT.	DATI TECNICI	RESISTENZA (N/5 cm)	CODICE	STAMPA	1 rotolo da 30 €/mq	da 29 a 15 mt €/mq	da 14 a 1 mt €/mq
INTER Cast BLOCKOUT	opaco	440	1,12	30	36*36 250*250 D	1800/1030	CT-BK440-11L3	  	4,53	6,51	6,77
	opaco	440	1,37	30	36*36 250*250 D	1800/1030	CT-BK440-13L3	  	4,53	6,51	6,77
	opaco	440	1,60	30	36*36 250*250 D	1800/1030	CT-BK440-16L3	  	4,53	6,51	6,77
	opaco	610	1,12	30	28*28 500*500 D	1850/1350	CT-BK610-11L3	  	5,37	7,72	8,03
	opaco	610	1,37	30	28*28 500*500 D	1850/1350	CT-BK610-13L3	  	5,37	7,72	8,03
	opaco	610	1,60	30	28*28 500*500 D	1850/1350	CT-BK610-16L3	  	5,37	7,73	8,04

PRODOTTO	FINITURA	PESO (g/m²)	H. CM.	MT.	DATI TECNICI	RESISTENZA (N/5 cm)	CODICE	STAMPA	1 rotolo da 30 €/mq	da 29 a 15 mt €/mq	da 14 a 1 mt €/mq
INTER Cast MESH COATED  	opaco	300	1,12	30	12*12 1000*1000 D	1250/1100	CT-MS300-11L3-FR	  	4,26	6,13	6,37
	con liner										
	opaco con liner	300	1,37	30	12*12 1000*1000 D	1250/1100	CT-MS300-13L3-FR	  	4,26	7,99	6,37
	opaco con liner	300	1,60	30	12*12 1000*1000 D	1250/1100	CT-MS300-16L3-FR	  	4,26	6,13	6,37
									1 rotolo da 50 €/mq	da 49 a 11 mt €/mq	da 10 a 1 mt €/mq
	opaco con liner	300	3,20	50	12*12 1000*1000 D	1250/1100	CT-MS300-32L5-FR	  	4,26	6,13	6,37

PRODOTTO	FINITURA	PESO (g/m²)	H. CM.	MT.	DATI TECNICI	RESISTENZA (N/5 cm)	CODICE	STAMPA	1 rotolo da 30 €/mq	da 29 a 15 mt €/mq	da 14 a 1 mt €/mq
 FRONTLIT LAMINATO	opaco high smooth	440	1,12	30	18*12 300*500 D	650/590	BL-FLHS440-11L3	  	2,37	3,41	3,55
	opaco high smooth	440	1,37	30	18*12 300*500 D	650/590	BL-FLHS440-13L3	  	2,37	3,41	3,55
	opaco high smooth	440	1,60	30	18*12 300*500 D	650/590	BL-FLHS440-16L3	  	2,37	3,41	3,55
									1 rotolo da 50 €/mq	da 49 a 11 mt €/mq	da 10 a 1 mt €/mq
	opaco high smooth	440	1,12	50	18*12 300*500 D	650/590	BL-FLHS440-11L5	  	2,37	3,41	3,55
	opaco high smooth	440	1,37	50	18*12 300*500 D	650/590	BL-FLHS440-13L5	  	2,37	3,41	3,55
	opaco high smooth	440	1,60	50	18*12 300*500 D	650/590	BL-FLHS440-16L5	  	2,37	3,41	3,55



Eco-solvent



Latex



UV



Disponibili su richiesta con certificazione EN13501-1